

Revised 10/10/2006

MATERIAL SAFETY DATA SHEET

1. CHEMICAL IDENTIFICATION

<u>Product/Common Name</u>	<u>Formula</u>	<u>Hazardous</u>
NanoLinK™ (4-FB) Magnetic Beads	Mixture	No
Date Revised: 3/22/2007		

2. COMPOSITION/INGREDIENTS

	<u>Approx. % (w/v)</u>	<u>Hazardous</u>
Chemical Name: Amino and Carboxylate-modified polystyrene microparticles modified with succinimidyl- 4-formyl benzoate	0.61	No
Chemical Name: 4-formyl benzoate	<0.01	No
Molecular Formula: C ₁₂ H ₉ NO ₅ MW 247.2		
Molecular Weight: 247.2		
RTECS ID: WZO440000		
Chemical Name: Fe ₂ O ₃ -Fe ₃ O ₄ (Magnetite)	0.420	No
RTECS ID: N07400000		
Chemical Name: Sodium Azide (preservative)	0.05	Yes
Chemical Name: water	98.91	No

3. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Brown aqueous suspension that may settle
Percent Purity: 1%
Boiling Point: 212F, 100C
Melting Point: NA
Specific gravity: 1.4-1.5
Freezing Point: NA
pH: NA
Solubility in water: suspension
Vapor Density: 0.624 @ 80 °F
Vapor Pressure: 17.5 mm Hg @ 20 °C

5. REACTIVITY

Stability: Stable when stored 4°C –25 °C (room temperature), (Conditions to avoid) may coagulate if frozen

at 32°F, 0°C or below. Dried resin is combustible and can raise dust.

Incompatibility: Addition of organic solvents may cause coagulation

Hazardous Decomposition Components: If burned, produces dense black smoke and noxious gases (carbon monoxide and hydrocarbons)

5. EXPOSURE CONTROLS/EMPLOYEE PROTECTION

Wear appropriate chemically-resistant gloves, safety goggles, and other protective clothing. Safety shower and eye bath. Wash thoroughly after handling.

6. HAZARDS IDENTIFICATION

Precautionary Statement: this product is not considered to present a health hazard when handled using standard laboratory practices and general hygiene measures, i.e wash hands thoroughly after handling.

Medical Conditions Aggravated:

Primary Routes of Entry:

PEL: NA

TLV: NA

LD50: NA

Carcinogenicity: NA

Toxicity: NA

RTECS #: NA

Acute Effects: NA

Chronic Effects: NA

Target Organs: NA

7. FIRST AID MEASURES

Eyes: Immediately flush eyes with copious amounts of water for at least 15 minutes

Skin: Immediately wash skin with soap and copious amounts of water

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen

Ingestion: If swallowed, wash out mouth with water provided person is conscious. Call a physician.

Other: Wash contaminated clothing before re-use

8. FIRE FIGHTING MEASURES

Upper Flammable Limit: Not applicable

Lower Flammable Limit: Not applicable

Upper Explosion Limit:

Lower Explosion Limit:

Flashpoint:

Autoignition Temperature:

Fire Extinguishing Media : Water fog, dry resin only.

Unusual Fire/Explosion Data: The dried resin is combustible, similar to wood. Burning the dry resin emits dense, black smoke. As latex, material is not combustible.

9. ACCIDENTAL RELEASE

Wear chemical safety goggles and latex gloves. Contain spill with absorbent material. Dispose of absorbent material in an appropriate container. Avoid drying or desiccating the product which could raise dust.

10. HANDLING AND STORAGE

Store at 4-8 °C.

11. WASTE DISPOSAL

This product contains 0.05% sodium azide. Sodium azide can react with copper or lead plumbing to form highly explosive metal azides. Upon disposal, flush with a large volume of water to prevent azide build-up. Sodium azide may be harmful if swallowed. In the event of oral exposure and the person is still conscious, rinse mouth out with copious amounts of water. In all cases, immediately contact a physician. Observe all federal, state, and local environmental regulations for disposal of plastic (polystyrene-based) solid waste. Dispose of product in accordance with all applicable Federal, State, and local environmental regulatory regulations.

Solulink, Inc. believes the above information to be accurate, but not necessarily all inclusive, and thus should only be used as a guide in the handling and use of this material. The data in this MSDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Solulink, Inc. shall not take responsibility for any damage resulting from handling or from contact with the above product. The information in this material safety data sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated thereunder 29 CFR § 1910.1200.