

Solulink, Incorporated
9853 Pacific Heights Blvd, Ste H
San Diego, California 92121

Phone: (858) 625-0670
Fax: (858) 546-0020

DATE: October 18, 2006

MATERIAL SAFETY DATA SHEET

1. CHEMICAL IDENTIFICATION

Chemical Name: **4-Nitrobenzaldehyde**
Catalog number: S-2001
Molecular Formula: $C_7H_5NO_3$
Molecular Weight: 151.1

2. COMPOSITION/INGREDIENTS

CAS Number: 555-16-8
Components: single compound

3. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: white solid
Percent Purity: >95%
Boiling Point: NA
Melting Point: NA
Freezing Point: NA
pH: NA
Solubility: NA
Vapor Density: NA
Vapor Pressure: NA

4. REACTIVITY

Stability: stable desiccated
Incompatibility: hydrolyzes in water
Hazardous Decomposition Components:

5. EXPOSURE CONTROLS/EMPLOYEE PROTECTION

Wear appropriate NIOSH/MSHA-approved respirator, chemical-resistant gloves, safety goggles, and other protective clothing. Safety shower and eye bath required. Mechanical exhaust required. Wash thoroughly after handling.

6. HAZARDS IDENTIFICATION

Precautionary Statement:
Medical Conditions Aggravated:
Primary Routes of Entry:
PEL: NA
TLV: NA
LD50: NA
Carcinogenicity: NA

| | |
|------------------|----|
| Toxicity: | NA |
| RTECS #: | NA |
| Acute Effects: | NA |
| Chronic Effects: | NA |
| Target Organs: | NA |

7. FIRST AID MEASURES

Eyes: Immediately flush eyes with copious amounts of water for at least 15 minutes

Skin: Immediately wash skin with soap and copious amounts of water

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen

Ingestion: If swallowed, wash out mouth with water provided person is conscious. Call a physician.

Other: Wash contaminated clothing before re-use

8. FIRE FIGHTING MEASURES

Upper Flammable Limit: NA

Lower Flammable Limit: NA

Upper Explosion Limit: NA

Lower Explosion Limit: NA

Flashpoint: NA

Auto ignition Temperature: NA

Fire Extinguishing Media: NA

Unusual Fire/Explosion Data: NA

9. ACCIDENTAL RELEASE

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Sweep up, place in a bag, and hold for waste disposal. Avoid raising dust. Ventilate area and wash spill site after material pickup is complete.

10. HANDLING AND STORAGE

Store desiccated at or below room temperature.

11. WASTE DISPOSAL

Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations.

Solulink, Inc. believes the above information to be accurate, but not necessarily all inclusive, and thus should only be used as a guide in the handling and use of this material. The data in this MSDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Solulink, Inc. shall not take responsibility for any damage resulting from handling or from contact with the above product. The information in this material safety data sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated thereunder 29 CFR § 1910.1200.